





Heyco® Shorty Universal Bushings

- Absorbs vibration, cushions and insulates cables, tubing, hoses or shafts with limited internal clearance.
- Molded of 6/6 "Nylon".
- Fingertip pressure snap-locks the bushing into its mounting hole.
- Flexible "shutters" adjust to accommodate and support any shape from .125" (3,2mm) to a maximum diameter of .750" (19,0mm).

PANEL DIMENSIONS				PART NO.	DESCRIPTION	PART DIMENSIONS					
Maximum Thickness		Mounting Hole Diameter				Black	Maximum Inside Diameter		A Head Diameter		B Overall Height
in.	mm.	in.	mm.					in.	mm.	in.	mm.
.062	1,6	.500	12,7	2858	SUB 500	.312	7,6	.600	15,2	.250	6,4
.062	1,6	.625	15,9	2861	SUB 625	.437	11,1	.729	18,5	.250	6,4
.062	1,6	.750	19,1	2862	SUB 750	.500	12,7	.859	21,8	.250	6,4
.062	1,6	.875	22,2	2863	SUB 875	.560	14,2	.937	23,8	.250	6,4
.062	1,6	1.000 ^{+.01} _{-.00}	25,4	2864	SUB 1000	.750	19,0	1.063	27,0	.453	11,5

Standard Color: Black. Consult factory for color matching, prices, and minimum order quantities.





Heyco® Universal Bushings

- Flexible "shutters" adjust to accommodate and support any shape from .125" (3,2mm) to a maximum diameter of 1.062" (26,9mm).
- Absorbs vibration, cushions and insulates cables, tubing, hoses or shafts with limited internal clearance.
- Fingertip pressure snap-locks the bushing into its mounting hole.

PANEL DIMENSIONS				PART NO.	DESCRIPTION	PART DIMENSIONS					
Maximum Thickness		Mounting Hole Diameter				Black	Maximum Inside Diameter		A Head Diameter		B Overall Height
in.	mm.	in.	mm.					in.	mm.	in.	mm.
.125	3,2	.500	12,7	2055	UB-500	.312	7,6	.600	15,2	.385	9,8
.125	3,2	.625	15,9	2077	UB-625	.437	11,1	.718	18,3	.406	10,3
.125	3,2	.750	19,1	2089	UB-750	.500	12,7	.844	21,4	.390	9,9
.125	3,2	.812	20,6	2106	UB-812	.500	12,7	.890	22,6	.390	9,9
.125	3,2	.875	22,2	2119	UB-875	.562	14,3	.937	23,8	.453	11,5
.125	3,2	1.000	25,4	2137	UB-1000	.750	19,1	1.063	27,0	.453	11,5
.125	3,2	1.093	27,8	2157	UB-1093	.812	20,6	1.156	29,4	.453	11,5
.125	3,2	1.375	34,9	2184	UB-1375	1.000	25,4	1.490	37,8	.453	11,5
.125	3,2	1.500	38,1	2213	UB-1500	1.062	26,9	1.610	40,9	.450	11,4

Standard Color: Black. Consult factory for color matching, prices, and minimum order quantities. Locking fingers in fractional increments up to maximum panel thickness.



Quick Specs

Material: 6/6 "Nylon"
 Certifications: Recognized under the Component Program of Underwriters' Laboratories, File #E-15331
 Certified by Canadian Standards Association, File #LR-8919
 Flammability Rating: 94V-2
 Material Temperature Index: 125°C—Maximum temperature on part not to exceed 105°C