



# Heyco® Shorty Bushings

PANEL DIMENSIONS				PART NO.		DESCRIPTION	PART DIMENSIONS					
Maximum Thickness		Mounting Hole Diameter		Black	White		A Inside Diameter		B Head Diameter		C Overall Height	
in.	mm.	in.	mm.			in.	mm.	in.	mm.	in.	mm.	
.062	1,6	.187	4,7	<b>2800</b>	<b>2801</b>	B 187-125	.125	3,2	.250	6,4	.234	5,9
.062	1,6	.218	5,5	<b>2859</b>	<b>2860</b>	B 218-125	.125	3,2	.281	7,1	.234	5,9
.062	1,6	.281	7,1	<b>2853</b>	<b>2854</b>	B 281-218	.218	5,5	.343	8,7	.234	5,9
.062	1,6	.312	7,9	<b>2810</b>	<b>2811</b>	B 312-250	.250	6,3	.375	9,5	.234	5,9
.062	1,6	.343	8,7	<b>2856</b>	<b>2857</b>	B 343-218	.218	5,5	.406	10,3	.250	6,4
.062	1,6	.375	9,5	<b>2803</b>	<b>2804</b>	B 375-250	.250	6,3	.437	11,1	.250	6,4
.062	1,6	.406	10,3	<b>2806</b>	<b>2807</b>	B 406-281	.281	7,1	.468	11,9	.250	6,4
.062	1,6	.437	11,1	<b>2813</b>	<b>2814</b>	B 437-312	.312	7,9	.500	12,7	.250	6,4
.062	1,6	.468	11,9	<b>2817</b>	<b>2818</b>	B 468-343	.343	8,6	.53	13,5	.250	6,4
.062	1,6	.500	12,7	<b>2820</b>	<b>2821</b>	B 500-375	.375	9,5	.562	14,3	.250	6,4
.062	1,6	.531	13,5	<b>2824</b>	<b>2825</b>	B 531-406	.406	10,3	.593	15,1	.250	6,4
.062	1,6	.593	15,1	<b>2833</b>	<b>2834</b>	B 593-468	.468	11,9	.656	16,7	.250	6,4
.062	1,6	.625	15,9	<b>2827</b>	<b>2828</b>	B 625-500	.500	12,7	.703	17,9	.250	6,4
.062	1,6	.750	19,1	<b>2836</b>	<b>2837</b>	B 750-625	.625	15,9	.828	21,0	.250	6,4
.062	1,6	.781	19,8	<b>2844</b>	<b>2845</b>	B 781-625	.625	15,9	.859	21,8	.250	6,4
.062	1,6	.875	22,2	<b>2850</b>	<b>2851</b>	B 875-750	.750	19,0	.937	23,8	.250	6,4
.062	1,6	1.000 <sup>+010</sup> <sub>-000</sub>	25,4	<b>2847</b>	<b>2848</b>	B 1000-875	.879	22,3	1.06	27,0	.250	6,4

- Available in seventeen sizes for use in mounting holes from 3/16" (4,7mm) to 1" (25,4mm).
- Insulating feed-thru bushings for limited internal clearance (minimum .125" or 3,2mm) applications.
- Insulates and isolates electric or telecommunications cables as well as low RPM shafts and push-pull rods.
- Locking fingers hold securely after only fingertip pressure "snap-in" installation.



### LabKit No. 2 (Part #2999)

A convenient assortment of various bushings for prototype and laboratory use. Lid Card indicates mounting hole sizes and bushing IDs.

See page 3-33 for more details.



Standard Colors: Black or White. Consult factory for color matching, prices, and minimum order quantities. Locking fingers in fractional increments up to the maximum panel thickness.



<b>Material</b>	6/6 "Nylon"
<b>Certifications</b>	Recognized under the Component Program of Underwriters' Laboratories, File #E-15331
	Certified by Canadian Standards Association, File #LR-8919
<b>Flammability Rating</b>	94V-2
<b>Material Temperature Index</b>	125°C—Maximum temperature on part not to exceed 105°C

Quick Specs