





Thick Panel Glossy Plugs

- Closes unneeded panel holes and electrical knock-outs.
- Smooth, glossy head provides easy glide finish to the head.
- Locking fingers "snap" into holes with fingertip pressure for quick and easy installation.
- Withstands a push back force of 35 pounds.
- Available in 11 sizes for use in 1/2" (12,7mm) to 2" (50,8mm) diameter holes.



PANEL DIMENSIONS				PART NUMBER		DESCRIPTION	PART DIMENSIONS			
Maximum Thickness		Mounting Hole Diameter		Black	White		A Head Diameter		B Overall Height	
in.	mm.	in.	mm.							
.250	6,4	.500	12,7	2430	2431	GPT-500	.563	14,3	.562	14,3
.250	6,4	.625	15,9	3134*	3135*	GPT-625	.734	18,6	.562	14,3
.250	6,4	.750	19,1	3136*	3137*	GPT-750	.859	21,8	.562	14,3
.250	6,4	.875	22,2	3138	3139	GPT-875	.953	24,2	.562	14,3
.250	6,4	1.000	25,4	3140	3141	GPT-1000	1.125	28,6	.562	14,3
.250	6,4	1.093-1.125	27,8-28,6	3142	3143	GPT-1093	1.218	30,9	.562	14,3
.250	6,4	1.187	30,2	3144	3145	GPT-1187	1.312	33,3	.562	14,3
.250	6,4	1.375	34,9	2432	2433	GPT-1375	1.468	37,3	.562	14,3
.250	6,4	1.500	38,1	2428	2429	GPT-1500	1.620	41,2	.562	14,3
.250	6,4	1.750	44,5	2436	2437	GPT-1750	1.875	47,6	.562	14,3
.250	6,4	2.000	50,8	2438	2439	GPT-2000	2.157	54,8	.562	14,3

Standard Colors: Black or White. Consult factory for color matching, prices, and minimum order quantities. Locking fingers in fractional increments up to the maximum panel thickness. *Depicts single panel thickness design



Quick Specs

Material	6/6 "Nylon"
Certifications	Recognized under the Component Program of Underwriters' Laboratories, File #E-15331 Certified by Canadian Standards Association, File #LR-8919
Flammability Rating	94V-2
Material Temperature Index	125°C—Maximum temperature on part not to exceed 105°C