




Heyco® Glossy Plugs

PANEL DIMENSIONS				PART NO.		DESCRIPTION	PART DIMENSIONS			
Maximum Thickness		Mounting Hole Diameter		Black	White		A Head Diameter		B Overall Height	
in.	mm.	in.	mm.				in.	mm.	in.	mm.
.062	1,6	.187	4,7	2590*	2591*	DP-187***	.250	6,4	.234	5,9
.062	1,6	.250	6,4	2600*	2601*	G-250	.312	7,9	.312	7,9
.062	1,6	.312	7,9	2610*	2611*	G-312	.375	9,5	.312	7,9
.125	3,2	.375	9,5	2620	2621	G-375	.468	11,9	.406	10,3
.125	3,2	.437	11,1	2630	2631	G-437	.531	13,5	.406	10,3
.125	3,2	.500	12,7	2640	2641	G-500	.563	14,3	.406	10,3
.125	3,2	.562	14,3	2650	2651	G-562	.656	16,7	.406	10,3
.125	3,2	.625	15,9	2660	2661	G-625	.734	18,6	.406	10,3
.125	3,2	.750	19,1	2680	2681	G-750	.859	21,8	.406	10,3
.125	3,2	.875	22,2	2700	2701	G-875	.953	24,2	.453	11,5
.125	3,2	1.000	25,4	2710	2711	G-1000	1.125	28,6	.453	11,5
.125	3,2	1.093 1.125	27,8 28,6	2720	2721	G-1093	1.218	30,9	.453	11,5
.125	3,2	1.187	30,1	2730	2731	G-1187	1.312	33,3	.453	11,5
.125	3,2	1.250	34,9	2760	2761	G-1375	1.468	37,2	.453	11,5
.125	3,2	1.500	38,1	2770	2771	G-1500	1.609	40,8	.453	11,5
.125	3,2	1.750	44,4	2780	2781	G-1750	1.875	47,6	.453	11,5
.125	3,2	2.000	50,8	2795	2796	G-2000	2.157	54,8	.453	11,5



Standard Colors: Black or White. Consult factory for color matching, prices, and minimum order quantities. Locking fingers in fractional increments up to the maximum panel thickness.

*Depicts single panel thickness design.


***Domed glossy finish head tapers to a thin edge.



SINGLE PANEL THICKNESS DESIGN*



MULTIPLE PANEL THICKNESS DESIGN



- Closes unneeded panel openings.
- Smooth, glossy head provides easy glide and shiny finish.
- Seventeen sizes for use in 3/16" (4,7mm) to 2" (50,8mm) diameter holes.
- Locks firmly in panel up to 1/8" (3,2mm) thick. { *1/16" (1,6mm) }
- Quick and easy installation.



LabKit No. 3 (Part #2997)

Perfect for product design departments, experimental labs, and for all prototype work. LabKit contains an assortment of the most popular sizes of hole, vent, and pry out plugs. Pertinent information on each size is attached inside the box lid.

See page 3-33 for more details.



Material Certifications	6/6 "Nylon" Recognized under the Component Program of Underwriters' Laboratories, File #E-15331
Flammability Rating	94V-2
Material Temperature Index	125°C—Maximum temperature on part not to exceed 105°C
	Certified by Canadian Standards Association, File #LR-8919

Quick Specs