





Heyco® Metric Snap Bushings

PANEL DIMENSIONS				PART NO.		DESCRIPTION	PART DIMENSIONS					
Maximum Thickness		Mounting Hole Diameter		Black	White		A Inside Diameter		B Head Diameter		C Overall Height	
in.	mm.	in.	mm.			in.	mm.	in.	mm.	in.	mm.	
.098	2,5	.630	16,0	2142	2143	MSB 16-12	.472	12,0	.728	18,5	.406	10,3
.098	2,5	.787	20,0	2144	2145	MSB 20-16	.630	16,0	.890	22,6	.406	10,3
.098	2,5	.984	25,0	2146	2147	MSB 25-19	.748	19,0	1.094	27,8	.453	11,5
.098	2,5	1.260	32,0	2148	2149	MSB 32-26	1.023	26,0	1.375	34,9	.453	11,5

Standard Colors: Black or White. Consult factory for color matching, prices, and minimum order quantities.



Consult Heyco for Colors Other Than Black or White


- Convert raw-edged holes to smooth ones.
- Locking fingers “snap” into holes with fingertip pressure.
- Withstands a push back force of 35 pounds.
- Four sizes for use in .630” (16,0mm) to 1.260” (32,0mm) diameter holes. For other metric sizes, consult Heyco.
- Locks firmly into panel up to .098” (2,5mm) thick.



Heyco® Metric Dome Plugs

CHASSIS DIMENSIONS				PART NO.		DESCRIPTION	PART DIMENSIONS			
Maximum Thickness		Mounting Hole Diameter		Black	White		A Head Diameter		B Overall Height	
in.	mm.	in.	mm.			in.	mm.	in.	mm.	
.098	2,5	.630	16,0	2128	2130	MDP 16	.728	18,5	.406	10,3
.098	2,5	.787	20,0	2131	2132	MDP 20	.890	22,6	.406	10,3
.098	2,5	.984	25,0	2133	2134	MDP 25	1.173	29,8	.453	11,5
.098	2,5	1.260	32,0	2135	2136	MDP 32	1.388	35,3	.453	11,5

Standard Colors: Black or White. Consult factory for color matching, prices, and minimum order quantities. Approximate Head Thickness: .063” (1,6mm).



Consult Heyco for Colors Other Than Black or White

- Closes unneeded chassis holes.
- Convex, matte finish head tapers to a thin edge.
- Four sizes for use in .630” (16,0mm) to 1.260” (32,0mm) diameter holes. For other metric sizes, consult Heyco.
- Locks firmly into panel up to .098” (2,5mm) thick.
- Quick and easy installation.

Material	Type 6/6 “Nylon”
Certifications	Recognized under the Component Program of Underwriters’ Laboratories File #E-15331 Certified by the Canadian Standards Association File #LR-8919
Flammability Rating	94V-2
Material Temperature Index	125°C–Maximum temperature on part not to exceed 105°C.

Quick Specs