




Heyco® Thick Panel Knock-Out Seals

- Plugs electrical knockouts.
- Molded in gray color to resemble galvanized steel.
- Six trade sizes fit 1/2" to 2" knockout holes for panels up to 1/4" thick.
- Locks firmly in boxes up to 1/4" thick.
- Installs quickly with fingertip pressure (no tool required).
- Economical.

PANEL DIMENSIONS				PART NO.	DESCRIPTION	PART DIMENSIONS			
Maximum Thickness		Mounting Hole Diameter				A Head Diameter		B Overall Height	
in.	mm.	in.	mm.	Silver Gray					
.250	6,4	.875	22,2	3991	KOST 1/2	1.015	25,8	.562	14,3
.250	6,4	1.093	27,8	3992	KOST 3/4	1.218	31,0	.562	14,3
.250	6,4	1.375	34,9	3993	KOST 1	1.500	38,1	.562	14,3
.250	6,4	1.750	44,5	3994	KOST 1-1/4	1.906	48,4	.562	14,3
.250	6,4	2.000	50,8	3995	KOST 1-1/2	2.140	54,4	.579	14,7
.250	6,4	2.500	63,5	4002	KOS 2	2.750	69,9	.750	19,1

Standard Color: Silver Gray.
 Locking fingers in fractional increments up to the maximum panel thickness.
 Approximate Head Thickness: .063" (1,6mm). Thickness may vary.



Quick Specs

Material	6/6 "Nylon"
Certifications	Recognized under the Component Program of Underwriters' Laboratories, File #E-15331 Certified by Canadian Standards Association, File #LR-8919
Flammability Rating	94V-2
Material Temperature Index	125°C—Maximum temperature on part not to exceed 105°C