




Heyco® Knock-Out Seals

PANEL DIMENSIONS				TRADE SIZE	PART NO.	DESCRIPTION	PART DIMENSIONS			
Maximum Thickness		Mounting Hole Diameter					A Head Diameter	B Overall Height		C Head Thickness
in.	mm.	in.	mm.		Silver Gray		in.	mm.	in.	mm.
.125	3,2	.875	22,2	1/2	3997	KOS 1/2	1.015	25,8	.453	11,5
.125	3,2	1.093	27,8	3/4	3998	KOS 3/4	1.218	31,0	.453	11,5
.125	3,2	1.375	34,9	1	3999	KOS 1	1.500	38,1	.453	11,5
.125	3,2	1.750	44,5	1-1/4	4000	KOS 1-1/4	1.906	48,4	.453	11,5
.125	3,2	2.000	50,8	1-1/2	4001	KOS 1-1/2	2.140	54,4	.453	11,5
.250	6,4	2.500	63,5	2	4002	KOS 2	2.750	69,9	.750	19,1

Standard Color: Silver Gray. Locking fingers in fractional increments up to the maximum panel thickness. Approximate Head Thickness: .063" (1,6mm).

Material	6/6 "Nylon"
Certifications	Recognized under the Component Program of Underwriters' Laboratories, File #E-15331 Certified by Canadian Standards Association, File #LR-8919
Flammability Rating	94V-2
Material Temperature Index	125°C—Maximum temperature on part not to exceed 105°C



- Plugs electrical knock-outs.
- Molded in gray color to resemble galvanized steel.
- Six trade sizes fit 1/2" to 2" knock-out holes.
- Locks firmly in boxes up to 1/8" thick (1/4" thick for KOS 2).
- Installs quickly with fingertip pressure (no tool required).
- Economical.



Heyco® Liquid Tight Knock-Out Seals

CHASSIS DIMENSIONS				PART NO.	DESCRIPTION	PART DIMENSIONS					
Maximum Thickness		Mounting Hole Diameter				Black	A Head Diameter		B Overall Height		C Head Thickness
in.	mm.	in.	mm.		in.	mm.	in.	mm.	in.	mm.	
.125	3,2	.875	22,2	3833	KOS-LT 1/2	1.281	32,5	.500	12,7	.359	9,1
.125	3,2	1.093	27,8	3835	KOS-LT 3/4	1.531	38,9	.546	13,9	.390	9,9
.125	3,2	1.375	34,9	3837	KOS-LT 1	1.796	45,6	.562	14,3	.421	10,7

Standard Color: Black.



- V0 Flammability rating.
- Oil tight, rain tight, submersible.
- Three trade sizes fit 1/2" to 1" knock-out holes.
- Locks firmly in boxes from .030" (0,8mm) to .125" (3,2mm) thick.
- Installs with fingertip pressure (no tool required).



Material	Neoprene-Hardness: 50 Shore A
Certifications	Listed Under Underwriters' Laboratories, File #E-28430 Certified by Canadian Standards Association, File #LR-81067
Flammability Rating	94V-0
Ingress Protection	Rated for use in NEMA 4, Enclosures IP 67 PER EN 60529

Quick Specs