




Heyco® Vent Plugs

PANEL DIMENSIONS				PART NO.		DESCRIPTION	No. of Vent Holes	PART DIMENSIONS			
Maximum Thickness		Mounting Hole Diameter		Black	White			A Head Diameter		B Overall Height	
in.	mm.	in.	mm.					in.	mm.	in.	mm.
.125	3,2	.500	12,7	2637	2638	VP-500	4	.578	14,7	.406	10,3
.125	3,2	.625	15,8	2657	2658	VP-625	5	.734	18,7	.406	10,3
.125	3,2	.750	19,1	2677	2678	VP-750	8	.906	23,0	.406	10,3
.125	3,2	.875	22,2	2697	2698	VP-875	9	1.015	25,8	.453	11,5
.125	3,2	1.000	25,4	2707	2708	VP-1000	9	1.203	30,6	.453	11,5
.125	3,2	1.093 1.125	27,8 28,6	2726	2727	VP-1093	9	1.218	30,9	.453	11,5
.125	3,2	1.187	30,2	2736	2737	VP-1187	10	1.312	33,3	.453	11,5
.125	3,2	1.250	31,8	2743	2744	VP-1250	10	1.375	34,9	.453	11,5
.125	3,2	1.250	31,8	2797	—	SVP-1250	4	1.375	34,9	.453	11,5
.125	3,2	1.375	34,9	2756	2757	VP-1375	11	1.500	38,1	.453	11,5
.125	3,2	1.500	38,1	2766	2767	VP-1500	13	1.671	42,4	.453	11,5
.125	3,2	1.750	44,5	2776	2777	VP-1750	13	1.906	48,4	.453	11,5
.125	3,2	2.000	50,8	2786	2787	VP-2000	19	2.140	54,4	.468	11,9
.250	6,4	2.500	63,5	2793	2794	VP-2.5	19	2.718	69,0	.750	19,1
.250	6,4	3.000	76,2	2458	2459	VP-3.0	26	3.171	80,5	.750	19,1
.250	6,4	3.500	88,9	2467	2468	VP-3.5	38	3.656	92,9	.750	19,1
.250	6,4	4.000	101,6	2476	2477	VP-4.0	48	4.156	105,6	.750	19,1

- Permits the passage of air for ventilation and heat dissipation.
- Convex, matte finish head tapers to a thin edge.
- Sixteen sizes for use in 1/2" (12,7mm) to 4" (101,6mm) diameter holes.
- VP-500 through VP-875 have 3/32" (2,4mm) diameter vent holes. All other sizes have 1/8" (3,2mm) diameter vents.
- Locks firmly into panel up to 1/4" (6,4mm) thick.
- Quick and easy installation with only fingertip pressure.



Standard Colors: Black or White (where indicated). Consult factory for color matching, prices, and minimum order quantities. Locking fingers in fractional increments up to the maximum chassis thickness. Approximate Head Thickness: .063" (1,6mm).



Material 6/6 "Nylon"
Certifications Recognized under the Component Program of Underwriters' Laboratories, File #E-15331
 Certified by Canadian Standards Association, File #LR-8919
Flammability Rating 94V-2
Material Temperature Index 125°C—Maximum temperature on part not to exceed 105°C

Quick Specs