



PG Nylon Threaded Plugs

- Molded of shock resistant polystyrol.
- Working temperature range: -20°C to +80°C.
- Protection Class IP 50.
- Color is light gray Ral 7035.

PART NO.	THREAD TYPE/SIZE	A Head Diameter		B Overall Height	
		in.	mm.	in.	mm.
Gray					
3405	PG 7	.551	14,0	.315	8,0
3407	PG 9	.787	20,0	.354	9,0
3402	PG 11	.866	22,0	.354	9,0
3412	PG 13	.984	25,0	.374	9,5
3414	PG 16	1.063	27,0	.374	9,5
3416	PG 21	1.299	33,0	.472	12,0
3418	PG 29	1.732	44,0	.472	12,0
3415	PG 36	2.165	55,0	.551	14,0
3417	PG 48	2.717	69,0	.709	18,0



Metric Nylon Threaded Plugs

PART NO.	THREAD TYPE/SIZE	A Head Diameter		B Overall Height	
		in.	mm.	in.	mm.
Gray					
3403	M12 x 1,5	.591	15,0	.394	10,0
3404	M16 x 1,5	.787	20,0	.472	12,0
3406	M20 x 1,5	.945	24,0	.472	12,0
3408	M25 x 1,5	1.181	30,0	.591	15,0
3409	M32 x 1,5	1.457	37,0	.630	16,0
3410	M40 x 1,5	1.811	46,0	.709	18,0
3411	M50 x 1,5	2.165	55,0	.787	20,0
3413	M63 x 1,5	2.717	69,0	.787	20,0

For black, add suffix B to metric threaded plug part numbers and consult factory for price and availability.

