




Heyco® Polyurethane Adhesive Backed Bumpers

Hemispherical



Clear	PART NO.				DESCRIPTION	PART SPECIFICATIONS/DIMENSIONS				
	Black	White	Gray	Brown		A		B		Pieces per Pad
						Diameter		Height		
in.	mm.	in.	mm.							
N040	N140	N240	N340	N440	HBA 250-06	.25	6,4	.06	1,6	578
N007	N107	N207	N307	N407	HBA 335-09	.34	8,6	.09	2,3	450
N012	N112	N212	N312	N412	HBA 375-15	.38	9,7	.15	3,8	200
N002	N102	N202	N302	N402	HBA 440-20	.44	11,2	.20	5,1	242
N015	N115	N215	N315	N415	HBA 620-31	.62	15,7	.31	7,9	128
N008	N108	N208	N308	N408	HBA 700-38	.70	17,8	.38	9,7	98
N039	N139	N239	N339	N439	HBA 750-08	.75	19,1	.08	2,0	84

Recognized under the Component Program of Underwriters' Laboratories File #E196663.



- Bumpers can be attached to a wide variety of surfaces; aluminum, ceramic, formica, glass, painted surfaces, polyethylene, polypropylene, vinyl, and steel.
- Quick and easy installation—simply peel off backing and press into place. With no holes to drill, and no screws or rivets needed, adhesive backed bumpers will save you time and money.
- Adhesive backed bumpers are nonmarking, nonstaining, skid, and scratch resistant.
- Surface must be clean, dry, and free of grease, oil, and other common solvents to obtain maximum adhesion. Clean surfaces with low strength solvents such as Isopropyl Alcohol or Heptane.
- Recommended storage guidelines: temperature range 40 to 75°F (4 to 24°C), humidity range 40 to 60%.
- Clear and white parts have an anti-yellowing agent.
- Clear bumpers have acrylic-based pressure sensitive adhesive with an end use temperature of 0°F–250°F (-20°C–120°C). The pigmented products are available in 4 colors and have a rubber-based pressure sensitive adhesive with an end use temperature of 0°F–180°F (-20°C–82°C).