




Heyco-Flex™ VI Light Duty Equipment/OEM Hose



PART NO.	DESCRIPTION	PART DIMENSIONS		VAC. RATE AT 70°F	STANDARD COIL LENGTH ft/coil	BEND RADIUS
		A Inside Diameter in.	B Outside Diameter in.			
8399	HF6 375 OEMH 100' coil clear	.375	.563	15	100	.50
8440	HF6 500 OEMH 100' coil clear	.500	.688	15	100	.50
8441	HF6 625 OEMH 100' coil clear	.625	.813	10	100	.63
8442	HF6 750 OEMH 100' coil clear	.750	.969	10	100	.75
8443	HF6 1000 OEMH 100' coil clear	1.000	1.250	8	100	1.00
8444	HF6 1250 OEMH 100' coil clear	1.250	1.500	22	100	1.00
8445	HF6 1500 OEMH 100' coil clear	1.500	1.813	20	100	2.00
8446	HF6 2000 OEMH 100' coil clear	2.000	2.375	18	100	2.00

Standard Color: Clear with white helix.
Consult Heyco for sizes larger than 2".

- 3/8" thru 2" sizes.
- Extremely flexible PVC with a convoluted surface.
- Lightweight.
- Suitable for light duty drainage, air, vacuum gravity feed, and other equipment/OEM applications.



Heyco-Flex™ VII Braided Tubing



PART NO.	DESCRIPTION	PART DIMENSIONS		W.P. (psi) at 70°F	STANDARD COIL LENGTH ft/coil
		A INSIDE DIAMETER in.	B OUTSIDE DIAMETER in.		
8361	HF7 187 BT 300' coil	.18	.41	275	300
8362	HF7 250 BT 300' coil	.25	.44	275	300
8363	HF7 312 BT 300' coil	.31	.49	275	300
8364	HF7 375 BT 300' coil	.37	.59	275	300
8365	HF7 500 BT 300' coil	.50	.75	275	300
8366	HF7 625 BT 200' coil	.62	.87	275	200
8367	HF7 750 BT 200' coil	.75	1.02	250	200
8368	HF7 1000 BT 200' coil	1.00	1.30	150	200
8369	HF7 1250 BT 100' coil	1.25	1.63	100	100
8370	HF7 1500 BT 100' coil	1.50	1.93	80	100
8371	HF7 2000 BT 100' coil	2.00	2.50	70	100

- 3/16" thru 2" sizes.
- Clear, flexible, reinforced PVC.
- Suitable for high working pressure under harsh conditions.
- For use in industrial applications, factory air lines, automation machinery, pneumatic lines, and water mains/feeds.
- For use with barb style hose connectors.
- See page 0-15 for our Part No. 8340 cutting tool.

