



Heyco-Flex™ V Slit Tubing

- Twelve sizes 1/8" to 1-1/2".
- Slit design allows side entry and encirclement of pre-assembled harnesses and capillary tubes.
- All nylon construction resists salt water, weak acids, gasoline, alcohol, oil, grease, and common solvents.
- Heyco-Flex V is lightweight and flexible, yet durable enough to meet your wire management requirements.
- Unique slit design allows for wire breakouts.
- Quick installation; cuts with utility knife, PVC cutter or Heyco cutting tool #8340. See page 0-15.
- Consult Heyco for slit tubing cut to length.
- Material: Polyamide 6 "Nylon".
- Flammability Rating: 94HB.

NOMINAL DIAMETER	PART NO. Black	DESCRIPTION	PART DIMENSIONS						ROLL LENGTH	
			A Outside Diameter		B Inside Diameter		C Wall Thickness Range		ft.	M
			in.	mm.	in.	mm.	in.	mm.		
1/8"	1634A	HF5 1/8	.260	6,6	.168	4,3	.007-.019	0,18-0,48	100	31
1/4"	1635A	HF5 1/4	.390	9,9	.288	7,3	.007-.019	0,18-0,48	100	31
11/32"	1636A	HF5 5/16	.500	12,7	.342	8,7	.007-.019	0,18-0,48	100	31
3/8"	1637A	HF5 3/8	.532	13,5	.415	10,5	.007-.019	0,18-0,48	100	31
7/16"	1638A	HF5 7/16	.613	15,6	.440	11,2	.007-.019	0,18-0,48	100	31
1/2"	1639A	HF5 1/2	.660	16,8	.511	13,0	.007-.019	0,18-0,48	100	31
5/8"	1641A	HF5 5/8	.806	20,5	.663	16,8	.007-.019	0,18-0,48	100	31
3/4"	1642A	HF5 3/4	.928	23,6	.790	20,1	.007-.019	0,18-0,48	100	31
1"	1643A	HF5 1	1.073	27,3	.917	23,3	.007-.019	0,18-0,48	100	31
1-1/16"	1644A	HF5 1-1/16	1.215	30,9	1.010	25,6	.007-.019	0,18-0,48	100	31
1-1/4"	1646A	HF5 1-1/4	1.500	38,1	1.295	32,9	.007-.019	0,18-0,48	100	31
1-1/2"	1649A	HF5 1-1/2	1.734	43,9	1.465	37,2	.007-.019	0,18-0,48	100	31

Standard Color: Black.

**Consult Heyco
for White or Other
Colors.**

