



Heyco® Strain Relief Mounting Hole Plugs

Standardize Panel Design and Fill Unused Holes







- Closes unused strain relief mounting holes or other chorded or Double "D" holes punched or molded with two opposing flats.
- Convex, matte finish head tapers to a thin edge.
- Locks firmly in panels up to 1/8" (3,2mm) thick.
- Quick and easy installation.
- Use our rectangular plug #1890 to fill unneeded Lockit™ Strain Relief mounting holes.

PANEL DIMENSIONS						PART NO.		DESCRIPTION	PART DIMENSIONS			
Maximum Thickness		D Long Axis		C Short Axis		Black	White		A Head Dimension		B Overall Height	
in.	mm.	in.	mm.	in.	mm.			in.	mm.	in.	mm.	
.125	3,2	.437	11,1	.390	9,9	2488	2489	DD-437-390	.531	13,5	.406	10,3
.125	3,2	.500	12,7	.445	11,3	2491	2492	DD-500-445	.578	14,7	.406	10,3
.125	3,2	.562	14,3	.530	13,5	2494	2495	DD-562-530	.656	16,7	.406	10,3
.125	3,2	.625	15,9	.550	14,0	2497	2498	DD-625-550	.718	18,2	.406	10,3
.125	3,2	.750	19,0	.625	15,9	2503	2504	DD-750-625	.921	23,4	.453	11,5
.125	3,2	.875	22,2	.770	19,6	2509	2510	DD-875-770	1.016	25,8	.453	11,5
.099	2,5	.512	13,0	.453	11,5	1890	1891	RP-115-130*	.578	14,7	.403	10,2

Standard Colors: Black or White. Consult Heyco for other colors. Consult factory for color matching, prices, and minimum order quantities.

*Rectangular plug to fill unneeded Lockit Strain Relief Mounting holes/not UL or CSA.

Locking finger steps designed in fractional increments.



PART NUMBERS 1890/1891

Quick Specs

Material	6/6 "Nylon"
Certifications	Recognized under the Component Program of Underwriters' Laboratories File #E-15331 Certified by the Canadian Standards Association File #LR-8919
Flammability Rating	94V-2
Material Temperature Index	125°C—Maximum temperature on part not to exceed 105°C