



# Heyco® Knock-Out Adapters For Strain Relief Bushings



Will Adapt These Strain Reliefs to Fit an .875" (22.2mm.) Diameter Hole.	PART NO.	DESCRIPTION	LUG LENGTH	
			in.	mm.
3L-1, 3P-4, 3P-5, 3W-1, 13-1	7561	A-21F	.500	12,7
4K-1, 4K-4, 4K-6, 4L-1 4L-4, 5L-1, 5P3-4, 5P-4 5P-7, 5S-1, 6W-1, 14-1 15-1, 5M-3	7562	A-22F	.500	12,7
4L-4, 5L-1, 5P3-4, 5P-4, 5P-7, 5S-1, 6W-1, 14-1, 15-1, 5M-3	7563	A-23F	.500	12,7
6K-5, 6L-1, 6P2-5, 6P3-4 6P3-5, 6P3-7, 6P-4, 6P-5 6P-7, 10-2, 11-2, 11K-2	7567	A-25F	.500	12,7
2P-4, 2P-5, 5K-4, 5W-1, 16-1, 2L-1, 2M-4	7570	A-28F	.500	12,7
300-1	7571	A-40	.375	9,5
20-1, 20L-1, 30-1	7572	A-41	.500	12,7
7P-2, 7P-7, 17-2	7573	A-42F	.375	9,5
302-1	7577	A-43	.375	9,5
23-1, 33-1	7578	A-44	.376	9,6
7K-2, 7W-2, 8L-1, 8P-2, 24-1, 31-2, 34-2	7579	A60F	.500	12,7
4K-1, 4K-4, 4K-6, 4L-1, 4L-4, 5L-1, 5P3-4, 5P-4, 5P-7, 5S-1, 6W-1, 14-1, 15-1, 5M-3	7580	A-12F	.250	6,3

- Made of zinc-plated steel.
- Converts trade size knock-out holes to diameters suitable for strain relief bushings.
- Allows for standardization of panel design since various strain relief bushings sizes can be adapted to one panel hole size.
- Allows for the mounting of strain relief bushings into unusually thick panel.
- Adapters mount into 1/2" knock-outs (7/8" or 22,2 mm nominal diameter).

**A-10 Adapter Pliers (Part #0024)** For quick and easy locking of adapters.

