



Heyco® Wire Protector Terminal Blocks

Consult Heyco for Other Pole Configurations



Screw to Screw-With Wire Protector Flap

BODY STYLE	WIRE SIZE AWG	mm ²	AMPS North America	POLES	PART NO.		DESCRIPTION	Screws (Metric)	PART DIMENSIONS												
					Natural	FR Brown			A		B		C		D		E		F		
									(12) Poles	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.
Low Profile*	12-22	25	20	2	9389	9419	TB 0B-WP-2P	M 2,6	3.69	93,6	.64	16,2	.61	15,4	.11	2,8	.32	8,0	.11	2,8	
				3	9390	9420	TB 0B-WP-3P														
				12	9393	9423	TB 0B-WP-12P														
Raised Base	10-20	4	30	2	9394	9424	TB 1B-WP-2P	M 3,0	4,58	116,4	.73	18,6	.67	17,0	.14	3,6	.39	10,0	.14	3,6	
				3	9395	9425	TB 1B-WP-3P														
				12	9398	9428	TB 1B-WP-12P														
	8-14	6	50	2	9399	9429	TB 2B-WP-2P	M 3,5	5,26	133,5	.87	22,2	.82	20,8	.17	4,2	.45	11,5	.15	3,7	
				3	9400	9430	TB 2B-WP-3P														
				12	9403	9433	TB 2B-WP-12P														
		6-10	16	55	2	9404	9434	TB 3B-WP-2P	M 4,0	6,89	175,0	.99	25,2	1,04	26,3	.23	5,8	.59	15,0	.20	5,1
					3	9405	9435	TB 3B-WP-3P													
					12	9408	9438	TB 3B-WP-12P													

Standard Color: Natural. Flame retardant brown available at extra charge.

Notes:

Part No. 9299 fixing pin can be used to mount all terminal blocks, with panel thickness limitations—consult Heyco.

*Body Style indicates our standard offering/stocked product, and the alternate body style is available for all configurations—consult Heyco.

- Wire protector flap allows the use of STRANDED or SOLID wire with no crimp terminals and no soldering required.
- Allows standardization of the SOLID WIRE Cordset. Input and output wires are always secured with a screw.
- Modern low profile design occupies less “real estate” inside the appliance.
- No exposed metal parts. “Dead front” designed safety.
- Pressure clamp connectors are supplied in the open position, ready to accept single or multiple solid conductors.
- All sizes are rated at 300 volts (450 volts in Europe).
- Metal parts feature galvanized steel screws and galvanized brass inserts.
- Standard natural color parts are molded of type 6 “Nylon”. Flammability classification 94V-2; temperature index 115°C (except TB 3B-140°C).
- Available in 94V-0 flame retardant (FR), glass-filled nylon 6/6 material. Temperature index 140°C (except TB 3P-170°C).
- Recognized under the Component Program of Underwriters’ Laboratories File #E-197025.
- Certified by Canadian Standards Association File #LR-210961.
- Approved.
- **Part No. 9299** fixing pin available for mounting terminal blocks.

