





CPB PREBULBED SLOTTED BODY SERIES

CPB SERIES



- The CPB series offers a large grip range for installation into single, variable or multiple thickness materials.
- Large backside footprint provides increased pull out resistance.
- Designed to be installed in thin plastics without distorting the base material.
- Inch body
- Inch and metric threads



Installs into single, variable, or multiple thickness materials.

UNIFIED THREAD (UNIT - INCHES)

Part Number (Steel)	Thread Size	Grip Range		HD		L	HT	D	IL	Hole Size
		Min.	Max.	Min.	Max.	±.015	±.005	Max.	Ref.	+.006/- .000
CPB2-1024-175♦	10-24 UNC	.020	.175	.490	.510	.828	.038	.329	.410	.336
CPB2-1024-320♦	10-24 UNC	.175	.320	.490	.510	.921	.038	.329	.410	.336
CPB2-1032-175	10-32 UNF	.020	.175	.490	.510	.828	.038	.329	.410	.336
CPB2-1032-320	10-32 UNF	.175	.320	.490	.510	.921	.038	.329	.410	.336
CPB2-2520-280	1/4-20 UNC	.020	.280	.610	.645	1.000	.059	.382	.505	.390
CPB2-2520-500	1/4-20 UNC	.280	.500	.610	.645	1.234	.059	.382	.505	.390
CPB2-3118-280	5/16-18 UNC	.020	.280	.740	.770	1.141	.062	.495	.570	.500
CPB2-3118-500	5/16-18 UNC	.280	.500	.740	.770	1.375	.062	.495	.570	.500

METRIC THREAD (UNIT - MILLIMETERS)

Part Number (Steel)	Thread Size	Grip Range		HD		L	HT	D	IL	Hole Size
		Min.	Max.	Min.	Max.	±0.38	±0.13	Max.	Ref.	+.15/- .000
CPB2-580-4.45♦	M5x0.8 ISO	0.50	4.45	12.45	12.95	21.03	0.96	8.35	10.00	8.55
CPB2-580-8.1	M5x0.8 ISO	4.45	8.10	12.45	12.95	23.80	0.96	8.35	10.00	8.55
CPB2-610-7.1	M6x1.0 ISO	0.50	7.10	15.50	16.38	25.40	1.50	9.70	12.80	10.00
CPB2-610-12.7♦	M6x1.0 ISO	7.10	12.70	15.50	16.38	31.32	1.50	9.70	12.80	10.00
CPB2-8125-7.1	M8x1.25 ISO	0.50	7.10	18.80	19.65	28.95	1.57	12.57	14.48	12.70
CPB2-8125-12.7♦	M8x1.25 ISO	7.10	12.70	18.80	19.65	34.90	1.57	12.57	14.48	12.70

♦ Non-Standard Part: Minimum order quantity required after depletion of stock. Please contact Sherex for current availability.

PART NUMBERING SYSTEM

CPB Specifications

Material:

Steel 1008/1010

Aluminum 6061

RoHS Compliant Finishes:

Zinc Plated-Yellow Trivalent Chromate
per Sherex SFS-01-001, SC2

Zinc Plated-Clear Trivalent Chromate
per Sherex SFS-01-001

Part Number

Example: CPB2-2520-280

CPB	2	2520	280	()
Product Style	2-Steel	Thread Size	Grip Range	Empty-Open End
Slotted Body	3-Aluminum			T-Clear Trivalent
Pre-bulbed				W-Wedge Head
				TR-Trim Head

Special finish or material available upon request

Grip range can be affected by parent material and hole size.
Sherex recommends trials installations to determine the proper grip range for the application.
Contact Sherex for details.
Contact Sherex for test data.

INSTALLATION TOOLING

CPB Series can be installed with our Hand Tools, Pneumatic Tools, and Hydro-Pneumatic Tools.
For additional tooling information see pages 39-44.

Sherex rivet nuts are compatible with the following hardware:

GRADE 2, GRADE 5, CLASS 8.8 and CLASS 9.8

Please contact Sherex when using other grade fasteners.

WEDGE HEAD

TRIM HEAD