



Phillips Flat Head, Hi-Low, Notched Threads, Diamond Point, Blue Ceramic Coating



Material Application: Attaches wood or metal to concrete, brick, cement block or masonry.

Size	Bulk Part No	Bulk Qty	Lbs*	Packaged Part No	Packaged Qty**	Submittal	Miami-Dade
3/16 x 1-1/4	CF320	5M	35	PCF320	500	View	
3/16 x 1-3/4	CF328	4M	39	PCF328	500	View	
3/16 x 2-1/4	CF336	2.5M	31	PCF336	500	View	View
3/16 x 2-3/4	CF344	2M	29	PCF344	500	View	View
3/16 x 3-1/4	CF352	1.5M	26	PCF352	500	View	View
3/16 x 3-3/4	CF360	1M	20	PCF360	500	View	View
3/16 x 4	CF364	1M	22	PCF364	500	View	View
1/4 x 1-1/4	CF420	3M	37	PCF420	500	View	
1/4 x 1-3/4	CF428	2M	33	PCF428	500	View	
1/4 x 2-1/4	CF436	1.5M	31	PCF436	500	View	View
1/4 x 2-3/4	CF444	1M	25	PCF444	500	View	View
1/4 x 3-1/4	CF452	1M	28	PCF452	500	View	View
1/4 x 3-3/4	CF460	.5M	17	PCF460	500	View	View
1/4 x 4	CF464	.5M	18	PCF464	500	View	View
1/4 x 5	CF480	.5M	22	N/A	N/A	View	View
1/4 x 6	CF496	.5M	26	N/A	N/A	View	View

**5 boxes packaged 100 per box. One drill bit included per box.

*Carton weights are approximate and may vary.

Features

- Notched threads for cutting into concrete, brick and cement block
- Hi-Low thread pattern creates higher pullout tolerances
- Diamond point design cuts and clears debris during installation for better thread engagement
- Blue ceramic coating exceeds 500/hrs. salt spray resistance
- ACQ compatible

Specifications



- Meets ASTM A 510 for carbon steel manufacturing
- Miami-Dade County Product Control Approved. NOA-15-0930.14



Slotted Indented Hex Washer Head, Hi-Low, Notched Threads, Diamond Point, Blue Ceramic Coating



Material Application: Attaches wood or metal to concrete, brick, cement block or masonry.

Size	Bulk Part No	Bulk Qty	Lbs*	Head Size	Packaged Part No	Packaged Qty**	Submittal	Miami-Dade
3/16 x 1-1/4	CH320	5M	41	1/4" A.F.	PCH320	500	View	
3/16 x 1-3/4	CH328	3M	32	1/4" A.F.	PCH328	500	View	
3/16 x 2-1/4	CH336	2.5M	32	1/4" A.F.	PCH336	500	View	View
3/16 x 2-3/4	CH344	2M	32	1/4" A.F.	PCH344	500	View	View
3/16 x 3-1/4	CH352	1.5M	28	1/4" A.F.	PCH352	500	View	View
3/16 x 3-3/4	CH360	1M	21	1/4" A.F.	PCH360	500	View	View
3/16 x 4	CH364	1M	23	1/4" A.F.	PCH364	500	View	View
1/4 x 1-1/4	CH420	3M	36	5/16" A.F.	PCH420	500	View	
1/4 x 1-3/4	CH428	2M	33	5/16" A.F.	PCH428	500	View	
1/4 x 2-1/4	CH436	1.5M	30	5/16" A.F.	PCH436	500	View	View
1/4 x 2-3/4	CH444	1M	25	5/16" A.F.	PCH444	500	View	View
1/4 x 3-1/4	CH452	1M	29	5/16" A.F.	PCH452	500	View	View
1/4 x 3-3/4	CH460	.5M	17	5/16" A.F.	PCH460	500	View	View
1/4 x 4	CH464	.5M	18	5/16" A.F.	PCH464	500	View	View
1/4 x 5	CH480	.5M	22	5/16" A.F.	N/A	N/A	View	View
1/4 x 6	CH496	.5M	26	5/16" A.F.	N/A	N/A	View	View

**5 boxes packaged 100 per box. One drill bit included per box.

*Carton weights are approximate and may vary.

Features

- Notched threads for cutting into concrete, brick and cement block
- Hi-Low thread pattern creates higher pullout tolerances
- Diamond point design cuts and clears debris during installation for better thread engagement
- Blue ceramic coating exceeds 500/hrs. salt spray resistance
- ACQ compatible

Specifications



- Meets ASTM A 510 for carbon steel manufacturing
- Miami-Dade County Product Control Approved. NOA-15-0930.14