




## HEYClip™ Optical Fiber Network Cable Holders



WIRE CAPACITY		MOUNTING HOLE DIAMETER			PART NO.		DESCRIPTION	OVERALL HEIGHT C		FOOTPRINT A x B	
in.	mm.	in.	mm.	DART STYLE	Natural	94V-2		94V-0	in.	mm.	in.
<b>For Round Mounting Holes</b> For panels from .031" (0,8 mm) to .079" (2,0 mm) thick											
.83 x .75	21,1 x 19,1	.187	4,8	1	<b>12150</b>	<b>12150F</b>	CH OF-282-48	1.25	31,8	.27 x 1.06	6,9 x 26,9
		.250	6,4	2	<b>12151</b>	<b>12151F</b>	CH OF-282-64				
1.13 x .99	28,7 x 25,1	.187	4,8	1	<b>12153</b>	<b>12153F</b>	CH OF-344-48	1.50	38,1	.27 x 1.35	6,9 x 34,3
		.250	6,4	2	<b>12154</b>	<b>12154F</b>	CH OF-344-64				
<b>For Square Mounting Holes</b> For panels from .031" (0,8 mm) to .079" (2,0 mm) thick											
.83 x .75	21,1 x 19,1	.374	9,5	4	<b>12156</b>	<b>12156F</b>	CH OF-282-95S	1.19	30,2	.27 x 1.06	6,9 x 26,9
		.307	7,8	3	<b>12161</b>	<b>12161F</b>	CH OF-344-78S				
1.13 x .99	28,7 x 25,1	.374	9,5	4	<b>12157</b>	<b>12157F</b>	CH OF-344-95S	1.44	36,6	.27 x 1.35	6,9 x 34,3
1.38 x 1.73	35,1 x 43,9	.374	9,5	4	<b>12158</b>	<b>12158F</b>	CH OF-550-95S	2.25	57,2	.27 x 1.69	6,9 x 42,9

Standard color natural.



- Smooth, rounded corners eliminate stress on delicate fiber optic wires.
- Gather and route fiber optic wires.
- Available for round and square mounting holes.




Style 1




Style 2



Style 3



Style 4



Material	Nylon 6/6
Flammability Rating	94V-2 and 94V-0
Temperature Range	32°F (0°C) to 185°F (85°C) (94V-2) 32°F (0°C) to 203°F (95°C) (94V-0)