HEYCO






- For clamping cable or tubing securely into place, especially in harsh environments.
- Smooth "coined clamp" edges prevent damage to cable insulation.
- Constructed from corrosion resistant 304 stainless steel.
- Coated parts are constructed from 304 stainless steel and coated with polyolefin a thermoplastic co-polymer.
- Coating provides a durable non-toxic, odorless coating that has very good low temperature flexibility and excellent electrical properties. This coating also has FDA food contact approval.
- All parts require a .203" (5,2 mm) mounting hole suitable for a #10 screw.
- Not for use in a marine salt water environment. Contact Heyco for alternative materials.
- DFARS Compliant



- Light to heavy duty steel clamp.
- E.P.D.M. cushion for electrical insulation and vibration absorption.
- Steel clamps are zinc electroplated for corrosion resistance.
- Color Silver with durable black cushion.






Heyco® Stainless Steel Cable Clamps

PART Dimension A		STANDARD		COATED				
		PART NO. DESCRIPTION		PART NO.	DESCRIPTION			
in.	mm.							
P Clamp Style								
.25	6,3	S3374	CC H 1/4 SS	S3324	CC H 1/4 SS Coated			
.38	9,5	S3376	CC H 3/8 SS	S3326	CC H 3/8 SS Coated			
.50	12,7	S3378	CC H 1/2 SS	\$3328	CC H 1/2 SS Coated			
.63	15,9	\$3380	CC H 5/8 SS	\$3330	CC H 5/8 SS Coated			
.75	19,1	S3382	CC H 3/4 SS	\$3332	CC H 3/4 SS Coated			
.88	22,2	S3384	CC H 7/8 SS	S3334	CC H 7/8 SS Coated			

Consult Heyco for additional sizes.





Heyco® Steel Cushion Clamps



MOUN HOLE in.	DIA. mm.	SCREW SIZE	PA DIMEN in.	SION A mm.	PART NO.	DESCRIPTION	
.650" (16,5 mm) Overall Width, .031" (0,8 mm) Steel Thickness							
.265	6,7	1/4	.187 .250 .312 .375 .437 .500 .562 .625 .687 .750 .875 1.000 1.125	4,7 6,3 7,9 9,5 11,1 12,7 14,3 15,9 17,4 19,1 22,2 25,4 28,6 31,8	12300 12301 12302 12303 12304 12305 12306 12307 12308 12309 12310 12311 12311 12312	CCSC L 3/16 CCSC L 1/4 CCSC L 5/16 CCSC L 3/8 CCSC L 7/16 CCSC L 1/2 CCSC L 9/16 CCSC L 5/8 CCSC L 11/16 CCSC L 3/4 CCSC L 7/8 CCSC L 1 CCSC L 1-1/8 CCSC L 1-1/8	
.750" (19,1 mm) Overall Width, .047" (1,2 mm) Steel Thickness							
.406	10,3	7/16	.250 .312 .375 .437 .500 .625 .687 .875 1.000	6,3 7,9 9,5 11,1 12,7 15,9 17,4 22,2 25,4 31,8	12331 12332 12333 12334 12335 12337 12338 12340 12341 12343	CCSC H 1/4 CCSC H 5/16 CCSC H 3/8 CCSC H 7/16 CCSC H 1/2 CCSC H 5/8 CCSC H 11/16 CCSC H 7/8 CCSC H 1 CCSC H 1-1/4	

	CC H	CCSC
Material	304 Stainless Steel	Zinc Plated Steel with an EPDM Sleeve