




## Heyco® Dome Plugs

Mounting Hole Diameter Range: .187" (4,7 mm) to 6.000" (152,4 mm)

- Close unneeded panel holes and electrical knockouts.
- Quick and easy installation.
- Convex, matte finish head tapers to thin edge (Except DP-187).
- Multiple sizes for use in .187" (4,7 mm) to 6.000" (152,4 mm) diameter holes.
- Lock firmly into panel up to .250" (6,4 mm) thick.
- Locking fingers in fractional increments up to the maximum panel thickness.
- Approximate Head Thickness: .062" (1,6 mm). Thickness may vary.
- For Snap-In Metric Dome Plugs see page 6-28.

MOUNTING HOLE DIAMETER in.   mm.	PART NO.			DESCRIPTION	PART DIMENSIONS				
	Black	White	Colors xx**		A Head Diameter in.   mm.		B Overall Height in.   mm.		
Single Locking Step for Panel Thickness up to .062" (1,6 mm)									
.187   4,7	<b>2590</b>	<b>2591</b>	2592xx	DP 187*	.25	6,4	.23	5,9	
.250   6,4	<b>2607</b> <b>2603</b>	<b>2608</b> <b>2604</b>	2609xx 2605xx	DP 250-040† DP 250	.31	7,9	.31	7,9	
.312   7,9	<b>2613</b>	<b>2614</b>	2615xx	DP 312	.38	9,5			
Multiple Locking Steps for Panel Thickness up to .125" (3,2 mm)									
.375   9,5	<b>2617</b>	<b>2618</b>	2619xx	DP 375	.47	11,9	.41	10,3	
.437   11,1	<b>2633</b>	<b>2634</b>	2635xx	DP 437	.53	13,5			
.500   12,7	<b>2643</b>	<b>2644</b>	2645xx	DP 500	.56	14,2			
.562   14,3	<b>2653</b>	<b>2654</b>	2655xx	DP 562	.66	16,7			
.625   15,9	<b>2663</b>	<b>2664</b>	2665xx	DP 625	.72	18,2			
.687   17,4	<b>2673</b>	<b>2674</b>	2675xx	DP 687	.78	19,8			
.750   19,1	<b>2683</b>	<b>2684</b>	2685xx	DP 750	.92	23,4			
.812   20,6	<b>2693</b>	<b>2694</b>	2695xx	DP 812	.99	25,1			
.875   22,2	<b>2703</b>	<b>2704</b>	2705xx	DP 875	1.02	25,8			
1.000   25,4	<b>2713</b>	<b>2714</b>	2715xx	DP 1000	1.20	30,6			
1.093 - 1.125   27,8 - 28,6	<b>2723</b>	<b>2724</b>	2725xx	DP 1093	1.22	30,9	.45	11,5	
1.187   30,1	<b>2733</b>	<b>2734</b>	2735xx	DP 1187	1.33	33,8			
1.250   31,7	<b>2740</b>	<b>2741</b>	2742xx	DP 1250	1.38	34,9			
1.375   34,9	<b>2753</b>	<b>2754</b>	2755xx	DP 1375	1.50	38,1			
1.500   38,1	<b>2763</b>	<b>2764</b>	2765xx	DP 1500	1.67	42,4			
1.750   44,5	<b>2773</b>	<b>2774</b>	2775xx	DP 1750	1.92	48,7			
2.000   50,8	<b>2783</b>	<b>2784</b>	2785xx	DP 2000	2.17	55,1			
Multiple Locking Steps for Panel Thickness up to .250" (6,4 mm)									
2.093 - 2.125   53,2 - 54,0	<b>2403</b>	<b>2404</b>	***	DP 2.093	2.34	59,9	.75	19,1	
2.250   57,2	<b>2411</b>	<b>2412</b>	2413xx	DP 2.25	2.48	63,0	.75	19,1	
2.500   63,5	<b>2790</b>	<b>2791</b>	2792xx	DP 2.5	2.71	68,8			
3.000   76,2	<b>2455</b>	<b>2456</b>	2457xx	DP 3.0	3.16	80,3	.74	18,8	
3.375   85,7	<b>2482</b>	<b>2483</b>	***	DP 3.375	3.66	92,9	.75	19,1	
3.500   88,9	<b>2464</b>	<b>2465</b>	2466xx	DP 3.5	3.66	92,9			
4.000   101,6	<b>2473</b>	<b>2474</b>	2475xx	DP 4.0	4.17	105,8	.71	18,0	
5.000   127,0	<b>2451</b>	<b>2452</b>	***	DP 5.0	5.24	133,0	.75	19,1	
6.000   152,4	<b>2453</b>	<b>2454</b>	***	DP 6.0	6.22	157,9	.78	19,8	



Standard colors black and white. Consult Heyco for other colors (see below)

\*Convex, glossy finish head.

\*\*xx indicates that, following the color match process, Heyco adds a two letter suffix to the Root Part No. shown. This suffix will identify your particular CUSTOM Color selection. Consult Heyco for molded nylon color chips for accurate matching. For details as well as information regarding our Stock Colors, see page 6-51.

\*\*\*Consult Heyco for root Part No.

† Max panel thickness is .040" (1,0 mm)

Quick Specs

Material	Nylon 6/6
Certifications	Recognized under the Component Program of Underwriters' Laboratories File E51579 Certified by the Canadian Standards Association File 8919
Flammability Rating	94V-2
Temperature Range	-40°F (-40°C) to 221°F (105°C)