



- For clamping cable or tubing securely into place, especially in **harsh environments**.
- Smooth “coined clamp” edges prevent damage to cable insulation.
- Constructed from corrosion resistant 304 stainless steel.
- Coated parts are constructed from 304 stainless steel and coated with polyolefin a thermoplastic co-polymer.
- Coating provides a durable non-toxic, odorless coating that has very good low temperature flexibility and excellent electrical properties. This coating also has **FDA food contact** approval.
- All parts require a .203” (5,2 mm) mounting hole suitable for a #10 screw.
- Not for use in a marine salt water environment. Contact Heyco for alternative materials.
- DFARS Compliant

## Heyco® Stainless Steel Cable Clamps

PART DIMENSION A		STANDARD		COATED	
in.	mm.	PART NO.	DESCRIPTION	PART NO.	DESCRIPTION
<b>P Clamp Style</b>					
.25	6,3	<b>S3374</b>	CC H 1/4 SS	<b>S3324</b>	CC H 1/4 SS Coated
.38	9,5	<b>S3376</b>	CC H 3/8 SS	<b>S3326</b>	CC H 3/8 SS Coated
.50	12,7	<b>S3378</b>	CC H 1/2 SS	<b>S3328</b>	CC H 1/2 SS Coated
.63	15,9	<b>S3380</b>	CC H 5/8 SS	<b>S3330</b>	CC H 5/8 SS Coated
.75	19,1	<b>S3382</b>	CC H 3/4 SS	<b>S3332</b>	CC H 3/4 SS Coated
.88	22,2	<b>S3384</b>	CC H 7/8 SS	<b>S3334</b>	CC H 7/8 SS Coated

Consult Heyco for additional sizes.




## Heyco® Steel Cushion Clamps

MOUNTING HOLE DIA.		SCREW SIZE	PART DIMENSION A		PART NO.	DESCRIPTION
in.	mm.		in.	mm.		
<b>.650” (16,5 mm) Overall Width, .031” (0,8 mm) Steel Thickness</b>						
.265	6,7	1/4	.187	4,7	<b>12300</b>	CCSC L 3/16
			.250	6,3	<b>12301</b>	CCSC L 1/4
			.312	7,9	<b>12302</b>	CCSC L 5/16
			.375	9,5	<b>12303</b>	CCSC L 3/8
			.437	11,1	<b>12304</b>	CCSC L 7/16
			.500	12,7	<b>12305</b>	CCSC L 1/2
			.562	14,3	<b>12306</b>	CCSC L 9/16
			.625	15,9	<b>12307</b>	CCSC L 5/8
			.687	17,4	<b>12308</b>	CCSC L 11/16
			.750	19,1	<b>12309</b>	CCSC L 3/4
			.875	22,2	<b>12310</b>	CCSC L 7/8
			1.000	25,4	<b>12311</b>	CCSC L 1
			1.125	28,6	<b>12312</b>	CCSC L 1-1/8
1.250	31,8	<b>12313</b>	CCSC L 1-1/4			
<b>.750” (19,1 mm) Overall Width, .047” (1,2 mm) Steel Thickness</b>						
.406	10,3	7/16	.250	6,3	<b>12331</b>	CCSC H 1/4
			.312	7,9	<b>12332</b>	CCSC H 5/16
			.375	9,5	<b>12333</b>	CCSC H 3/8
			.437	11,1	<b>12334</b>	CCSC H 7/16
			.500	12,7	<b>12335</b>	CCSC H 1/2
			.625	15,9	<b>12337</b>	CCSC H 5/8
			.687	17,4	<b>12338</b>	CCSC H 11/16
			.875	22,2	<b>12340</b>	CCSC H 7/8
			1.000	25,4	<b>12341</b>	CCSC H 1
			1.250	31,8	<b>12343</b>	CCSC H 1-1/4



- Light to heavy duty steel clamp.
- E.P.D.M. cushion for electrical insulation and vibration absorption.
- Steel clamps are zinc electroplated for corrosion resistance.
- Color - Silver with durable black cushion.



Quick Specs

	CC H	CCSC
Material	304 Stainless Steel	Zinc Plated Steel with an EPDM Sleeve