



**NO O-RING  
REQUIRED!**



## Heyco®-Tite Liquid Tight Cordgrips

**Straight-Thru, NPT Hubs with Integral Sealing Ring**


*The Ultimate in Liquid Tight Strain Relief Protection*

- Integral Sealing Ring ensures a superior seal at the clearance or threaded mounting hole location, every time.
- Widest range of approved cable diameters.
- IP 68 rated.
- Approved for **NEMA 4, 4X, 6 and 6P** applications.
- Ratchet design of sealing nut assembly provides superior anti-vibration protection and ensures a firm grip on the cable.
- Acme threads on body prevent skipping and speed installation.
- All nylon construction with Buna N or TPE sealing gland resists salt water, weak acids, gasoline, alcohol, oil, grease, and common solvents. (This feature is not assessed by UL.)
- Multiple sizes for flexible cord diameters ranging from .065" (1,7 mm) to 1.730" (44,0 mm).
- We recommend using the fitting with the smallest maximum diameter that will fit your application.
- **Locknuts not included.** For nylon locknut specifications or to order locknuts separately, see page 3-41.
- For Heyco Liquid Tight Threaded Plugs, see page 3-45.
- Consult Heyco for cordgrips molded in other colors.


**NEW!**

CABLE DIA. RANGE				PART NO.		DESCRIPTION	UL or RA	PART DIMENSIONS									
Minimum		Maximum		Black	Gray			A Clearance Hole Dia.	B Max. O.A. Length		C Thread Length		D Wrenching Nut Thk.		E Flat Size		
in.	mm.	in.	mm.				in.	mm.	in.	mm.	in.	mm.	in.	mm.			
.065	1,7	.210	5,3	<b>M4514</b>	<b>M4515</b>	RLTCG 1/4	RA	.540	13,7	1,29	32,8	.45	11,4	.21	5,3	.63	16,0
.115	2,9	.250	6,4	<b>M4516</b>	<b>M4517</b>	LTCG 1/4											
.065	1,7	.230	5,8	<b>M3458</b>	<b>M3459</b>	RLTCG 3/8	RA	.680	17,3	1,41	35,8	.49	12,4	.21	5,3	.83	21,1
.105	2,7	.315	8,0	<b>M3228</b>	<b>M3229</b>	LTCG 3/8											
.095	2,4	.290	7,4	<b>M4518</b>	<b>M4519</b>	RLTCG 1/2	UL	.875	22,2	1,70	43,2	.61	15,5	.21	5,3	.98	24,9
.170	4,3	.450	11,4	<b>M3231</b>	<b>M3232</b>	LTCG 1/2											
.180	4,6	.400	10,2	<b>M4520</b>	<b>M4521</b>	RLTCG LL 1/2	UL	.875	22,2	1,68	42,7	.44	11,2	.25	6,4	1,06	27,0
.260	6,6	.545	13,8	<b>M3200</b>	<b>M3201</b>	LTCG LL 1/2											
.250	6,4	.490	12,4	<b>M3460</b>	<b>M3461</b>	RLTCG 3/4	UL	1,040	26,4	2,00	50,8	.62	15,7	.25	6,4	1,30	33,0
.350	8,9	.630	16,0	<b>M3234GA</b>	<b>M3235GA</b>	LTCG 3/4											
.435	11,0	.705	17,9	<b>M3234</b>	<b>M3235</b>		UL	1,326	33,7	2,41	61,2	.76	19,3	.30	7,6	1,73	43,9
.490	12,4	.785	19,9	<b>M8439</b>	<b>M8440</b>	RLTCG 1											
.590	15,0	1,000	25,4	<b>M8437</b>	<b>M8438</b>	LTCG 1	UL	1,680	42,7	2,69	68,3	.78	19,8	.30	7,6	2,05	52,1
.787	20,0	1,020	26,0	<b>M4522</b>	<b>M4523</b>	RLTCG 1-1/4											
.865	22,0	1,260	32,0	<b>M4524</b>	<b>M4525</b>	LTCG 1-1/4	UL	1,920	48,8	2,81	71,3	.77	19,6	.36	9,1	2,47	62,7
1,000	25,4	1,240	31,5	<b>M3319</b>	<b>M3320</b>	RLTCG 1-1/2											
1,230	31,2	1,560	39,6	<b>M3317</b>	<b>M3318</b>	LTCG 1-1/2	UL	2,400	60,8	2,93	74,3	.79	20,1	.42	10,7	2,75	69,9
1,160	29,5	1,350	34,3	<b>M3323</b>	<b>M3324</b>	RLTCG 2											
1,450	36,8	1,730	44,0	<b>M3321</b>	<b>M3322</b>	LTCG 2											

Standard colors black and gray.



**SUGGESTED CLEARANCE HOLE FOR NONTHREADED MOUNTING**



**INTEGRAL SEALING RING**



*Quick  
Specs*

Material	Nylon 6/6 w/Buna N or TPE Sealing Gland
Certifications	<ul style="list-style-type: none"> <li>UL Listed under Underwriters' Laboratories File E51579</li> <li>RA Recognized under the Component Program of Underwriters' Laboratories File E51579</li> <li>SF Certified By Canadian Standard Association File 93876C</li> </ul>
Flammability Rating	94V-2-Consult factory for V0 material
Temperature Range	Static -40°F (-40°C) to 239°F (115°C) Dynamic -4°F (-20°C) to 212°F (100°C)
IP Rating	IP 68 (70 PSI, 5 BAR)