

Screw on Connectors

Finger Grip Connectors

Rated to 105°C (221°F) 600 volt max

Wire Size	Min.	Max	Part Number
-----------	------	-----	-------------

18-10	2 #18	3 #12	20584
-------	-------	-------	-------



18-8	3 #16	5 #12	20586
------	-------	-------	-------



18-8	3 #14 w/1 #18	3 #10	20588
------	---------------	-------	-------



14-6	2 #10 w/1 #12	1 #8 w/3 #10	20589
------	---------------	--------------	-------



For a wider range of coverage

22-8	3 #22	4 #12	20509
------	-------	-------	-------



Performance Plus Connectors

Rated 105°C (221°F) 300/600 Volt Max.
Replaces eight standard connectors

22-12	2 #22	2 #12	20540
-------	-------	-------	-------



18-8	2 #18	2 #8	20541
------	-------	------	-------



14-8	4 #14	5 #12	20542
------	-------	-------	-------



IDC Connectors

P/N	Photo	Wire Gauge	Max OD	How to use
20528 Yellow		(22-18 AWG)	1.52mm	
20527 Orange		(22-18AWG)	2.08mm	
20526 Red		(19-26AWG)	1.67mm	
20525 Red		(19-26AWG)	2.08mm	

Screw On Connectors

Rated 105°C (221°F) 300/600 Volt Max.

Wire Size	Min.	Max	Part Number
-----------	------	-----	-------------

22-14	2 #22	1 #16 w/1 #18	20501
-------	-------	---------------	-------



22-14	2 #22	3 #16	20502
-------	-------	-------	-------



22-14	1 #18 w/ 1 #20	4 #16 w/ 1 #20	20503
-------	----------------	----------------	-------



22-10	3 #20	2 #12 w/ 2 #14	20504
-------	-------	----------------	-------



22-10	3 #18	2 #20 w/2 #12	20506
-------	-------	---------------	-------



Ceramic Connectors

Rated 1000°F Max. 600 V

22-14	1 #14 w/ 1 #16	2 #14	20543
-------	----------------	-------	-------

22-10	3 #14	2 #10	20544
-------	-------	-------	-------



18-8	3 #14 w/ 3 #16	2 #8	20545
------	----------------	------	-------

Winged Grounding Connector

Color coded GREEN for quick identification as a grounding conductor for copper wire only.

Rated to 105°C (221°F) 1000 volt max

14-10	2 #14	5 #12	20583
-------	-------	-------	-------



W/P Connector Kits

Part Number: 5990-34
34 pc. Aqua W/P Connector Kit
20580 - 20 pc.
20581 - 10 pc.
20582 - 4 pc.

Purchase Individually

20580 22-12 Orange W/P Connector
20581 22-8 Red W/P Connector
20582 14-6 Blue W/P Connector

