


410 Stainless Steel Unslotted Indented Hex Washer Head, Self-Drilling, Passivated & Waxed




- Meets F.I.P.-1000.7 for torsional strength & drill speed
- Meets SAE J78 for performance & dimensional specifications

Material Application
Attaches metal or aluminum
to metal or aluminum.

Size	Pt	Bulk Part No	Bulk Qty	Lbs*	Drill Cap (in.)	5lb Part No	5lb Qty	1lb Part No	1lb Qty
8-18 x 1/2	2	4H808	5M	18	.035 - .100	4H808V	1,500	4H808I	300
8-18 x 3/4	2	4H812	5M	23	.035 - .100	4H812V	1,000	4H812I	200
8-18 x 1	2	4H816	4M	22	.035 - .100	4H816V	1,000	4H816I	200
10-16 x 1/2	2	4H1008	5M	26	.035 - .110	4H1008V	1,000	4H1008I	200
10-16 x 3/4	3	4H1012	4M	25	.035 - .176	4H1012V	1,000	4H1012I	200
10-16 x 1	3	4H1016	3M	24	.035 - .176	4H1016V	600	4H1016I	150
10-16 x 1-1/4	3	4H1020	2.5M	23	.035 - .176	4H1020V	500	4H1020I	100
10-16 x 1-1/2	3	4H1024	2M	21	.035 - .176	4H1024V	500	4H1024I	100
10-16 x 2	3	4H1032	1.5M	15	.035 - .176	4H1032V	400	4H1032I	80
12-14 x 3/4	3	4H1212	4M	33	.035 - .210	4H1212V	600	4H1212I	125
12-14 x 1	3	4H1216	3M	30	.035 - .210	4H1216V	500	4H1216I	100
12-14 x 1-1/4	3	4H1220	3M	35	.035 - .210	4H1220V	400	4H1220I	80
12-14 x 1-1/2	3	4H1224	2.5M	33	.035 - .210	4H1224V	400	4H1224I	80
12-14 x 2	3	4H1232	2M	33	.035 - .210	4H1232V	300	4H1232I	60
12-14 x 2-1/2	3	4H1240	1M	18	.035 - .210	4H1240V	250	4H1240I	50
14-14 x 3/4	3	4H1412	3M	38	.060 - .220	4H1412V	400	4H1412I	80
14-14 x 1	3	4H1416	2.5M	38	.060 - .220	4H1416V	350	4H1416I	70
14-14 x 1-1/4	3	4H1420	2M	35	.060 - .220	4H1420V	300	4H1420I	50
14-14 x 1-1/2	3	4H1424	1.5M	30	.060 - .220	4H1424V	250	4H1424I	50
14-14 x 2	3	4H1432	1M	25	.060 - .220	4H1432V	200	4H1432I	40
14-14 x 2-1/2	3	4H1440	.8M	24	.060 - .220	4H1440V	150	4H1440I	30
14-14 x 3	3	4H1448	.5M	17	.060 - .220	4H1448V	150	4H1448I	25
14-14 x 4	3	4H1464	.5M	22	.060 - .220	4H1464V	100	4H1464I	20
14-14 x 5	3	4H1480	.25M	13	.060 - .220	4H1480V	100	4H1480I	20
14-14 x 6	3	4H1496	.25M	16	.060 - .220	4H1496V	75	N/A	N/A
14-14 x 7/8 #12 HD	1	4H1	2.5M	30	.018 - .090	4H1V	400	4H1I	80

410 Stainless Steel Unslotted Indented Hex Washer Head, Self-Drilling, Passivated & Waxed




- Meets F.I.P.-1000.7 for torsional strength & drill speed
- Meets SAE J78 for performance & dimensional specifications

Material Application
Attaches metal or aluminum
to metal or aluminum.

Size	Pt	Bulk Part No	Bulk Qty	Lbs*	Drill Cap (in.)	5lb Part No	5lb Qty	1lb Part No	1lb Qty
12-24 x 1-1/4	5	4H5	3M	35	.125 - .500	4H5V	375	4H5I	100
12-24 x 1-1/2	5	4H52	2M	26	.125 - .500	4H52V	400	4H52I	80
12-24 x 2	5	4H53	1.5M	24	.125 - .500	4H53V	300	4H53I	60

410 Stainless Steel Unslotted Indented Hex Washer Head w/Bonded Washer, Self-Drilling, Passivated & Waxed




- Meets F.I.P.-1000.7 for torsional strength & drill speed
- Meets SAE J78 for performance & dimensional specifications
- Bonded washer creates leak proof seal

Material Application
Attaches metal or aluminum
to metal or aluminum.

Size	Pt	Bulk Part No	Bulk Qty	Lbs*	Drill Cap (in.)	Washer	5lb Part No	5lb Qty	1lb Part No	1lb Qty
12-24 x 1-1/4	5	4HA5	3M	42	.125 - .500	9/16" O. D.	4HA5V	375	4HA5I	75
12-24 x 1-1/2	5	4HA52	2M	33	.125 - .500	9/16" O. D.	4HA52V	300	4HA52I	60
12-24 x 2	5	4HA53	1.5M	29	.125 - .500	9/16" O. D.	4HA53V	250	4HA53I	50

410 Stainless Steel Unslotted Indented Hex Washer Head w/Bonded Washer, Self-Drilling, Passivated & Waxed




- Meets F.I.P.-1000.7 for torsional strength & drill speed
- Meets SAE J78 for performance & dimensional specifications
- Bonded washer creates leak proof seal

Material Application

Attaches metal or aluminum to metal or aluminum.

Size	Pt	Bulk Part No	Bulk Qty	Lbs*	Drill Cap (in.)	Washer	5lb Part No	5lb Qty	1lb Part No	1lb Qty
8-18 x 1/2	2	4HA808	5M	32	.035 - .100	1/2" O. D.	4HA808V	1,000	4HA808I	200
8-18 x 3/4	2	4HA812	5M	35	.035 - .100	1/2" O. D.	4HA812V	800	4HA812I	150
8-18 x 1	2	4HA816	4M	30	.035 - .100	1/2" O. D.	4HA816V	650	4HA816I	125
10-16 x 3/4	3	4HA1012	4M	35	.035 - .176	1/2" O. D.	4HA1012V	600	4HA1012I	125
10-16 x 1	3	4HA1016	3M	31	.035 - .176	1/2" O. D.	4HA1016V	500	4HA1016I	100
10-16 x 1-1/4	3	4HA1020	2.5M	30	.035 - .176	1/2" O. D.	4HA1020V	400	4HA1020I	100
10-16 x 1-1/2	3	4HA1024	2M	26	.035 - .176	1/2" O. D.	4HA1024V	400	4HA1024I	80
10-16 x 2	3	4HA1032	1.5M	22	.035 - .176	1/2" O. D.	4HA1032V	300	4HA1032I	60
12-14 x 3/4	3	4HA1212	3M	32	.035 - .210	9/16" O. D.	4HA1212V	500	4HA1212I	100
12-14 x 1	3	4HA1216	3M	37	.035 - .210	9/16" O. D.	4HA1216V	400	4HA1216I	80
12-14 x 1-1/4	3	4HA1220	2.5M	35	.035 - .210	9/16" O. D.	4HA1220V	350	4HA1220I	75
12-14 x 1-1/2	3	4HA1224	2.5M	39	.035 - .210	9/16" O. D.	4HA1224V	300	4HA1224I	70
12-14 x 2	3	4HA1232	1.5M	28	.035 - .210	9/16" O. D.	4HA1232V	250	4HA1232I	50
12-14 x 2-1/2	3	4HA1240	1M	22	.035 - .210	9/16" O. D.	4HA1240V	200	4HA1240I	40
14-14 x 3/4	3	4HA1412	3M	45	.060 - .220	5/8" O. D.	4HA1412V	300	4HA1412I	60
14-14 x 1	3	4HA1416	2.5M	44	.060 - .220	5/8" O. D.	4HA1416V	300	4HA1416I	50
14-14 x 1-1/4	3	4HA1420	2M	40	.060 - .220	5/8" O. D.	4HA1420V	250	4HA1420I	50
14-14 x 1-1/2	3	4HA1424	1.5M	34	.060 - .220	5/8" O. D.	4HA1424V	200	4HA1424I	40
14-14 x 2	3	4HA1432	1M	28	.060 - .220	5/8" O. D.	4HA1432V	180	4HA1432I	35
14-14 x 2-1/2	3	4HA1440	.8M	26	.060 - .220	5/8" O. D.	4HA1440V	160	4HA1440I	30
14-14 x 3	3	4HA1448	.5M	18	.060 - .220	5/8" O. D.	4HA1448V	125	4HA1448I	25
14-14 x 4	3	4HA1464	.5M	22	.060 - .220	5/8" O. D.	4HA1464V	100	4HA1464I	20
14-14 x 5	3	4HA1480	.25M	14	.060 - .220	5/8" O. D.	4HA1480V	100	4HA1480I	20
14-14 x 7/8 #12 HD	1	4HA1	2.5M	38	.018 - .090	5/8" O. D.	4HA1V	300	4HA1I	60

410 Stainless Steel Phillips Pan Head, Self-Drilling, Passivated & Waxed




- Meets F.I.P.-1000.7 for torsional strength & drill speed
- Meets SAE J78 for performance & dimensional specifications

Material Application

Attaches metal or aluminum to metal or aluminum.

Size	Pt	Bulk Part No	Bulk Qty	Lbs*	Drill Cap (in.)	5lb Part No	5lb Qty	1lb Part No	1lb Qty
6-20 x 3/8	2	4P63	20M	36	.035 - .090	4P63V	2,500	4P63I	500
6-20 x 1/2	2	4P64	15M	32	.035 - .090	4P64V	2,500	4P64I	500
8-18 x 1/2	2	4P84	10M	32	.035 - .100	4P84V	1,500	4P84I	300
8-18 x 5/8	2	4P85	8M	30	.035 - .100	4P85V	1,300	4P85I	250
8-18 x 3/4	2	4P86	7M	29	.035 - .100	4P86V	1,200	4P86I	250
8-18 x 1	2	4P88	6M	31	.035 - .100	4P88V	1,000	4P88I	200
8-18 x 1-1/4	2	4P810	5M	31	.035 - .100	4P810V	800	4P810I	160
8-18 x 1-1/2	2	4P812	4M	28	.035 - .100	4P812V	700	4P812I	150
10-16 x 1/2	2	4P104	8M	36	.035 - .110	4P104V	1,000	4P104I	200
10-16 x 3/4	3	4P106	6M	35	.035 - .176	4P106V	1,000	4P106I	200
10-16 x 1	3	4P108	4M	30	.035 - .176	4P108V	700	4P108I	150
10-16 x 1-1/2	3	4P110	3M	24	.035 - .176	4P110V	500	4P110I	100
10-16 x 2	3	4P116	2M	22	.035 - .176	4P116V	400	4P116I	80

410 Stainless Steel Phillips Flat Head, Self-Drilling, Passivated & Waxed



- Meets F.I.P.-1000.7 for torsional strength & drill speed
- Meets SAE J78 for performance & dimensional specifications
- For counter-sunk holes

Material Application


Attaches metal or aluminum to metal or aluminum.

Size	Pt	Bulk Part No	Bulk Qty	Lbs*	Drill Cap (in.)	5lb Part No	5lb Qty	1lb Part No	1lb Qty
6-20 x 3/4	2	4F63	10M	24	.035 - .090	4F63V	2,000	4F63I	400
6-20 x 1	2	4F64	8M	25	.035 - .090	4F64V	1,600	4F64I	300
8-18 x 3/4	2	4F83	7M	25	.035 - .100	4F83V	1,400	4F83I	250
8-18 x 1	2	4F84	6M	23	.035 - .100	4F84V	1,200	4F84I	200
8-18 x 1-1/2	2	4F86	4M	24	.035 - .100	4F86V	800	4F86I	160
10-16 x 3/4	3	4F103	6M	29	.035 - .176	4F103V	1,000	4F103I	200
10-16 x 1	3	4F104	4M	26	.035 - .176	4F104V	800	4F104I	160
10-16 x 1-1/2	3	4F106	2.5M	23	.035 - .176	4F106V	500	4F106I	100

*Carton weights are approximate and may vary.

Note: 5lb. and 1lb. Stainless Steel boxes sold per case or individually.

410 Stainless Steel Phillips Modified Truss (R/W) Head, Self-Drilling, Passivated & Waxed




- Meets F.I.P.-1000.7 for torsional strength & drill speed
- Meets SAE J78 for performance & dimensional specifications
- Medium degree of corrosion resistance

Material Application
Attaches metal or aluminum to metal or aluminum.

NEW PRODUCTS!

Size	Pt	Bulk Part No	Bulk Qty	Lbs*	Drill Cap (in.)	5lb Part No	5lb Qty	1lb Part No	1lb Qty
8-18 x 1/2	2	4M82	5M	18	.035 - .100	4M82V	1,300	4M82I	300
8-18 x 3/4	2	4M83	5M	23	.035 - .100	4M83V	1,000	4M83I	200
8-18 x 1	2	4M84	4M	22	.035 - .100	4M84V	800	4M84I	200
8-18 x 1-1/4	2	4M85	3M	20	.035 - .100	4M85V	750	4M85I	150
8-18 x 1-5/8	2	4M87	3M	24	.035 - .100	4M87V	600	4M87I	120
8-18 x 1-7/8	2	4M88	2M	18	.035 - .100	4M88V	500	4M88I	100
8-18 x 2-1/2	2	4M92	1.5M	17	.035 - .100	4M92V	375	4M92I	75
8-18 x 3	2	4M95	1.5M	20	.035 - .100	4M95V	375	4M95I	75
10-16 x 3/4	3	4M106	5M	27	.035 - .176	4M106V	1,000	4M106I	200

410 Stainless Steel Phillips/Square Drive Pancake Head, Strong-Shield Coated




- Meets ASTM C 1513 for cold-formed steel framing connections
- Meets F.I.P.-1000.7 for torsional strength & drill speed
- Meets SAE J78 for performance & dimensional specifications
- Rust/Acid Rain Protection
- ACQ Compatible
- Exceeds 1,000/hr. salt spray resistance

Material Application
Attaches panel clips to metal studs.



Size	Pt	Bulk Part No	Bulk Qty	Lbs*	Drill Cap (in.)	5lb Part No	5lb Qty	1lb Part No	1lb Qty
10-16 x 1	3	4PC8	4M	30	.035 - .176	4PC8V	650	4PC8I	125

410 Stainless Steel Star Drive Flat Head Reamer w/Wings, Strong-Shield Coated



- Meets ASTM C 1513 for cold-formed steel framing connections
- Meets F.I.P.-1000.7 for torsional strength & drill speed
- Meets SAE J78 for performance & dimensional specifications
- Rust/Acid Rain Protection
- ACQ Compatible
- Exceeds 1,000/hr. salt spray resistance

Material Application
Attaches wood to metal.



Size	Pt	Bulk Part No	Bulk Qty	Lbs*	Drill Cap (in.)	Wood Range	5lb Part No	5lb Qty	1lb Part No	1lb Qty
12-24 x 2-1/2	4	4RT212	1M	21	.110 - .375	1/2" - 1-1/2"	4RT212V	250	4RT212I	50
1/4-20 x 2-3/4	4	4RT234	.8M	24	.110 - .375	1/2" - 1-3/4"	4RT234V	160	4RT234I	30
1/4-20 x 3-1/4	4	4RT314	.5M	17	.110 - .375	3/4" - 2-1/4"	4RT314V	125	4RT314I	25

305 Stainless Steel Phillips Modified Truss (R/W) Head, Type '17'




- Superior penetration through a variety of woods
- Type '17' reduces wood splitting

Material Application
Attaches wood or light gauge metal to wood.

NEW PRODUCTS!

Size	Bulk Part No	Bulk Qty	Lbs*	5lb Part No	5lb Qty	1lb Part No	1lb Qty
8 x 3/4	X86MSS	5M	24	X86MSSV	1,000	X86MSSI	200
8 x 1	X88MSS	4M	22	X88MSSV	1,000	X88MSSI	200
8 x 1-1/4	X89MSS	3M	19	X89MSSV	750	X89MSSI	150
8 x 1-5/8	X90MSS	3M	25	X90MSSV	600	X90MSSI	120
8 x 1-7/8	X92MSS	2M	19	X92MSSV	500	X92MSSI	100
8 x 2-1/2	X95MSS	1.5M	18	X95MSSV	375	X95MSSI	75
8 x 3	X97MSS	1.5M	21	X97MSSV	375	X97MSSI	75

305 Stainless Steel Phillips/Square Drive Pancake Head



- Superior penetration through a variety of woods
- For use in non-magnetic applications
- High degree of corrosion resistance

Material Application
Attaches panel clips to wood studs.

Size	Bulk Part No	Bulk Qty	Lbs*	5lb Part No	5lb Qty	1lb Part No	1lb Qty
10-12 x 1	108PCSS	4M	27	108PCSSV	650	108PCSSI	125

305 Stainless Steel Phillips Bugle Head, Coarse Thread



- For fencing, decks, patio furniture, spas
- High degree of corrosion resistance

Material Application

Exterior wood screw for outdoor applications. Attaches wood to wood.

Size	Bulk Part No	Bulk Qty	Lbs*	5lb Part No	5lb Qty	1lb Part No	1lb Qty
8 x 1-1/4	814CSS	8M	40	814CSSV	1,000	814CSSI	200
8 x 1-5/8	815CSS	5M	31	815CSSV	750	815CSSI	150
8 x 2	820CSS	3.5M	25	820CSSV	500	820CSSI	100
8 x 2-1/2	822CSS	2.5M	23	822CSSV	400	822CSSI	100
8 x 3	830CSS	2M	22	830CSSV	400	830CSSI	80

305 Stainless Steel Star Drive Flat Head w/Nibs, Coarse Thread, Type '17'



- Star drive prevents cam out and stripping for improved driveability
- Superior penetration through a variety of woods
- High degree of corrosion resistance
- Type '17' reduces wood splitting

Material Application

Exterior wood screw for outdoor applications. Attaches wood to wood.

Size	Bulk Part No	Bulk Qty	Lbs*	5lb Part No	5lb Qty	1lb Part No	1lb Qty
8 x 1-1/4	XT814SS	5M	23	XT814SSV	1,000	XT814SSI	200
8 x 1-5/8	XT815SS	4M	23	XT815SSV	800	XT815SSI	160
8 x 2	XT820SS	3M	22	XT820SSV	700	XT820SSI	150
10 x 2-1/2	XT1022SS	2M	24	XT1022SSV	400	XT1022SSI	80
10 x 3	XT1030SS	1.5M	22	XT1030SSV	300	XT1030SSI	60
10 x 3-1/2	XT1031SS	1M	17	XT1031SSV	250	XT1031SSI	50
12 x 4	XT1240SS	1M	28	XT1240SSV	165	XT1240SSI	40

316 Stainless Steel Star Drive Flat Head w/Nibs, Coarse Thread, Type '17' **NEW ITEM!**



- Star drive prevents cam out and stripping for improved driveability
- Superior penetration through a variety of woods
- Maximum degree of corrosion resistance
- Type '17' reduces wood splitting

Material Application

Exterior wood screw for outdoor applications. Attaches wood to wood.

Size	Bulk Part No	Bulk Qty	Lbs*	5lb Part No	5lb Qty	1lb Part No	1lb Qty
10 x 2-1/2	XT1022MG	2M	25	XT1022MGV	400	XT1022MGI	80
10 x 3	XT1030MG	1.5M	22	XT1030MGV	300	XT1030MGI	60
10 x 3-1/2	XT1031MG	1M	17	XT1031MGV	250	XT1031MGI	50

305 Stainless Steel Square Drive Trim Head, Coarse Thread, Type '17'



- Superior penetration through a variety of woods
- Type '17' reduces wood splitting

Material Application

Exterior wood screw for attaching trim and rails to decks or fences.

Size	Bulk Part No	Bulk Qty	Lbs*	5lb Part No	5lb Qty	1lb Part No	1lb Qty
7 x 1-5/8	X1QSS	5M	29	X1QSSV	1,000	X1QSSI	200
7 x 2-1/4	X2QSS	3M	23	X2QSSV	600	X2QSSI	125
7 x 3	X3QSS	2M	21	X3QSSV	500	X3QSSI	100

305 Stainless Steel Star Drive Trim Head, Coarse Thread, Type '17'



- Superior penetration through a variety of woods
- Type '17' reduces wood splitting

Material Application

Exterior wood screw for attaching trim and rails to decks or fences.

Size	Bulk Part No	Bulk Qty	Lbs*	5lb Part No	5lb Qty	1lb Part No	1lb Qty
7 x 1-5/8	X1TSS	5M	29	X1TSSV	1,000	X1TSSI	200
7 x 2-1/4	X2TSS	3M	23	X2TSSV	600	X2TSSI	125
7 x 3	X3TSS	2M	21	X3TSSV	500	X3TSSI	100